

# GILA Series

## 2MV-70IR23E

### VANDALPROOF INFRARED DOME CAMERA



#### FEATURES

- 1/3" Ultra low-power, VGA CMOS image sensor
- 3.5" IR Dome Camera
- IR LED: 5 x 23 Pcs
- Lens: 3.6mm
- IR Distance: 20M
- On Screen Display (OSD)
- Auto White Balance (AWB)
- Back Light Compensation (BLC)
- Dimension: 105mm (R) x 72mm (H)

ITEM	2MV-70IR23E
Image Sensor	1/3" Ultra low-power, VGA CMOS image sensor
Horizontal Resolution	700 TV Lines
Pixels	PAL: 752(H) x 582(V) NTSC: 768(H) x 494(V)
TV System	PAL / NTSC
Minimum Illumination	0 Lux with IR LED on
Lens	3.6mm
Sync System	Internal, Negative Sync.
Scanning System	2.1 Interlace
IR Distance	20 Meters (with 23 Unit Infrared LED)
IR Status	Under 10 Lux by CDSCDS Auto
IR Power On	Control
S/N Ratio	≥48 dB (AGC Off)
White Balance	Auto
Gain Control	Auto
Back Light Compensation	On
Gamma Correction	0.45 Ω
Video Out	Composite Signal (1.0 Vp-p, 75)
Electronic Shutter Time	Auto: PAL: 1/50-1/100,000 sec. NTSC: 1/60-1/100,000 sec.
Operation Temperature	-10°C ~ +50°C / RH95% Max
Storage Temperature	-10°C ~ +50°C / RH95% Max
Power Source	12V DC / 400mA
Dimension	105mm (R) x 72mm (H)
Weight	370g

<b>700 TV LINES</b>	
<b>0.00 LUX</b>	
<b>IR LED</b>	
<b>Fixed LENS</b>	
<b>AWB</b> Auto White Balance	
<b>BLC</b> Back Light Compensation <b>OFF</b> <b>ON</b>	
<b>VOLTAGE</b> 12VDC	
<b>VANDALPROOF</b>	